


Cable Tie

Standard Cable Tie T18R and T30R Serie - Color



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2




Product Selection			Min. Ten ile Strength	Length (L)	Max. Ø Bundle	Width (W)	Color	Pkg. Qty.
Article No.	Part No.	Type						
T18R								
116-01811	T18R1C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Brown	100
111-01849	T18R1M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
111-01880	T18R2C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Red	100
111-01882	T18R2M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
116-01813	T18R3C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Orange	100
111-01877	T18R3M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
111-01896	T18R4C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Yellow	100
111-01898	T18R4M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
111-01853	T18R5C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Green	100
111-01855	T18R5M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
111-01842	T18R6C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Blue	100
111-01845	T18R6M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
116-01817	T18R7C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Purple	100
111-01888	T18R7M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
111-01857	T18R8C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	Gray	100
111-01859	T18R8M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
116-01819	T18R10C2	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)	White	100
111-01892	T18R10M4	T18R	18 lb (80)	4" (100)	.87" (22)	.10" (2.5)		1000
T30R								
116-03011	T30R1C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Brown	100
111-03038	T30R1M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03012	T30R2C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Red	100
111-03056	T30R2M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03013	T30R3C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Orange	100
111-03052	T30R3M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03014	T30R4C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Yellow	100
111-03065	T30R4M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03015	T30R5C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Green	100
111-03041	T30R5M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03016	T30R6C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Blue	100
111-03036	T30R6M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03017	T30R7C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Purple	100
111-03062	T30R7M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
116-03018	T30R8C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	Gray	100
111-03061	T30R8M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000
111-03019	T30R10C2	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)	White	100
116-03064	T30R10M4	T30R	30 lb (135)	5.9" (150)	1.38" (35)	.14" (3.5)		1000

In tallation tool - MK7, MK7HT, MK7P, MK9, MK9HT, MK9P. MK9 and MK9P tool cannot be u ed to in tall T18S cable tie .

Dimen ion are approximate and subject to technical change . U e **Part No.** for ordering and **Type** for pefication purpo e .

Standard Cable Tie T50R and T50L Serie - Color



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2



File# E64139



File# E64139

Product Selection

Article No.	Part No.	Type	Min. Tensile Strength		Length (L)		Max. Ø Bundle		Width (W)		Color	Pkg. Qty.
			lb.	(N)	in.	(mm)	in.	(mm)	in.	(mm)		
T50R												
116-05011	T50R1C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Brown	100
111-04852	T50R1M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05012	T50R2C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Red	100
111-04868	T50R2M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05013	T50R3C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Orange	100
111-04865	T50R3M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05014	T50R4C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Yellow	100
111-04892	T50R4M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05015	T50R5C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Green	100
111-04854	T50R5M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05016	T50R6C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Blue	100
111-04849	T50R6M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05017	T50R7C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	Purple	100
111-04877	T50R7M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
111-04870	T50R8C2	T50R	50 lb	(225)	7.9"	(202)	1.97"	(50)	.18"	(4.6)	Gray	100
111-04872	T50R8M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
116-05019	T50R10C2	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)	White	100
111-04879	T50R10M4	T50R	50 lb	(225)	7.9"	(200)	1.97"	(50)	.18"	(4.6)		1000
T50L												
111-05443	T50L1C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Brown	100
111-05444	T50L1M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05457	T50L2C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Red	100
111-05458	T50L2M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05451	T50L3C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Orange	100
111-05454	T50L3M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05467	T50L4C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Yellow	100
111-05468	T50L4M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05445	T50L5C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Green	100
111-00502	T50L5M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05431	T50L6C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Blue	100
111-05434	T50L6M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05464	T50L7C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Purple	100
111-00503	T50L7M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05461	T50L8C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	Gray	100
111-05462	T50L8M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000
111-05466	T50L10C2	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)	White	100
111-05465	T50L10M4	T50L	50 lb	(225)	15.35"	(390)	4.33"	(110)	.18"	(4.6)		1000

In tallation tool - MK7, MK7HT, MK7P, MK9, MK9HT, MK9P.

Dimension are approximate and subject to technical change. Use Part No. for ordering and Type for specification purpose.