



819 N. Highland Ave.
Los Angeles, CA 90038

Tel. (323) 465-2131, Fax (323) 465-3504
Visit us on the web at www.calrad.com



40-6110, 40-6110R


**ACTIVE BALUNS FOR
HDTV COMPONENT
OR PC VGA VIDEO,
ANALOG OR DIGITAL AUDIO
OVER 1 CAT5**




Units Sold Separately

Specifications:

DC Power 12Vdc 300ma
Max Input Video Level 1.5V p-p
High Slew Rate 2000V/us
Video Bandwidth 250 MHz
Audio Bandwidth 20-20Khz, +/- 1 db
Video Resolutions
PC: VGA, XGA, SXGA,
HDTV: 1080P, 1080I, 720P, 480P
Size: L-2.75" x W-2.6" x H-1"
Connectors: RJ45, 3.5mm, HD-DB15
Female Jacks
Includes: 1ft - 3.5mm Male to dual stereo
RCA adapter cable, 1ft. - HD-DB15 Male
to RCA Component Y, Pb, Pr male
adapter cable



Transmitter
40-6110



Receiver
40-6110R

'Differential Technology
Breaks Grounds from
Transmitter to Receiver'



No More Ground
Lift Adapters



No More 60 Hz Bars or
Interference Lines
In your pictures

