




VL650IRS	3.6mm lens, silver housing
VL650IRW	3.6mm lens, white housing
VL650IRVFS	2.8 - 12mm DC auto iris varifocal lens, silver housing
VL650IRVFW	2.8 - 12mm DC auto iris varifocal lens, white housing

Features

- Internal IR LEDs with anti-reflective technology
- Up to 65' IR range using 22 IR LEDs
- Tamper resistant construction
- IP67 rated for extreme weather applications
- Optional wall, ceiling & junction box adapters are available
- Available in white & silver housings
- Adjustability of camera functions through OSD
- 12VDC / 24VAC dual voltage operation
- 5 year warranty

Specifications

Image Sensor	1/3" color CCD
Resolution.....	600 TV lines
Minimum Illumination.....	0 lux with IR on, 0.1 lux with IR off
Effective Pixels	768 (H) x 494 (V)
Iris.....	VL650IR: Manual Iris VL650IRVF: Auto Iris
Electronic Shutter Speed.....	1/60 sec. – 1/100,000 sec.
Color.....	Yes
Effective IR Range.....	65'
Number of LEDs.....	22
LED IR Wave Length.....	850nm
S/N Ratio	More than 48dB
Gamma.....	0.45 typ.
Video Signal Output.....	1.0Vp-p, 75 Ohm
Scanning System.....	2:1 interlaced
Synchronization	Internal
Backlight Compensation.....	Auto / DWDR / HLC
AGC.....	Off / Low / Middle / High



CDS Sensor.....	Yes
TV System.....	NTSC
White Balance	ATW / AWC / Manual
Day & Night	Automatic / BW
Mirror	On / Off
Motion.....	On / Off (64 block)
Operating Temperature.....	14° F – 122° F
Storage Temperature.....	-4° F – 140° F
Power Consumption	450mA
Power Supply	12VDC / 24VAC (dual voltage) (power supply not included)
Housing	Aluminum
Dimensions.....	5.9" (Dia.) x 3.9" (H)
Weight	2.2 lbs.
Included in Package	BNC test lead, DC power pigtail, installation hardware

Optional Accessories



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 3/22/12