

Article Number: 590-10000



Description: Rite-On Self-Laminating Label Starter Kit, .75" x .75" x 3.0",

VL, White, 90/roll

Base Data		
	Local Order Number	RO175WP
	Туре	RO175WP
	Color	White (WH)
	Features and benefits	 Compact to easily fit in pants or shirt pockets. Dispenser can be reloaded over and over, making it cost effective to use. Dispenser edge allows easy removal of label liner. Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.
	Quantity Per	EA
	Product Description	HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.
	Global Part Name	RO175WP-100-WH
	Short Description	Rite-On Self-Laminating Label Starter Kit, .75" x .75" x 3.0", VL, White, 90/roll
Product Dimensions		
	Length L (Imperial)	0.75"
	Length L (Metric)	19.05mm
	Fixation Method	Pasting / Stick
	Self adhesive (Yes/No)	Yes
	Variant	Roller form
	Width W (Imperial)	0.75"
	Width W (Metric)	19.05mm
	Height H (Imperial)	.75"
	Height H (Metric)	19.05mm
	Height H2 (Imperial)	3.0"
	Height H2 (Metric)	76.20mm
	Bundle Diameter Min. (Imperial)	0.33"

generated on: 8/16/2017

590-10000



Product Dimensions Bundle Diameter Min. (Metric) 8.32mm Bundle Diameter Max. (Imperial) 0.7" Bundle Diameter Max. (Metric) 17.78mm Outside Diameter Min. (Imperial) 0.33" Outside Diameter Min. (Metric) 8.38mm	
Bundle Diameter Max. (Imperial) 0.7" Bundle Diameter Max. (Metric) 17.78mm Outside Diameter Min. (Imperial) 0.33"	
Outside Diameter Min. (Imperial) 0.33"	
Outside Diameter Min. (Metric) 8.38mm	
Outside Diameter Max. (Imperial) 0.7"	
Outside Diameter Max. (Metric) 17.78mm	
Material and Specifications	
Material Type 100, Vinyl (PVC), white (WH), self laminating	
Material Shortcut 100	
Adhesive Acrylic	
Adhesive Operating Temperature -51°F to +200°F (-46°C to +93°C)	
Minimum Application Temperature from +50°F (from +10°C)	
Operating Temperature -51°F to +200°F (-46°C to +93°C)	
ROHS Compliant Yes	
Logistic and Packaging	
Package Quantity (Imperial) 90	
Package Quantity (Metric) 90	
Customs Number(Schedule B) 3919102055	

generated on: 8/16/2017