

# Technical Data Sheet Communication Cables



2833 West Chestnut Street  
Washington, PA 15301  
Toll Free: (800) 245-4964  
Fax: (724) 222-6420  
www.westpenn-wpw.com



<b>PART NUMBER:</b>	<b>224</b>
<b>DESCRIPTION:</b>	18/2 STRANDED BARE COPPER CONDUCTORS, UNSHIELDED WITH AN OVERALL JACKET
<b>NEC RATING:</b>	CMR, NEC Article 800
<b>APPROVALS:</b>	(UL) C(UL) Listed or c(ETL)us Listed
<b>APPLICATION:</b>	Indoor for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control Circuits

## Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	7x26
Insulation Material	Polypropylene
Insulation Thickness	0.007" Nom.
Number of Conductors	2
Shield	None
Drain	None
Jacket Material	PVC
Jacket Thickness	0.017" Nom.
Overall Cable Diameter	0.156" Nom.
Approximate Cable Weight	16.1 Lbs/1M' Nom.
Flame Rating	UL 1666 Riser Flame Test

## Electrical & Environmental Properties:

Temperature Rating	-20°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	21.5pf/ft Nom.
DC Resistance per Conductor @ 20deg C	6.2 Ohms/1M' Nom.
Insulation Colors	Black ,Red
Jacket Color	Gray, Black, Brown, White
RoHS Compliant	Yes

## Mechanical Properties:

Max. Recommended Pull Tension	42 lbs.
Min. Bend Radius (Install)	1.6"



Specification Issue Date: 7/14

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.  
The Jacket is sequentially footmarked.  
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.