Special Function - Voltage Monitoring

R67 Series



Features


- Monitors AC Single Phase and DC Voltages
- Wide Range of User-Adjustable Pick-Up and Drop-Out Settings
- **LED Indicates Output Relay Status**
- Compact 8-Pin Octal Plug-In Case




OPERATION

Voltage Monitor Relays provide protection to equipment where an over or under voltage condition is potentially damaging. They monitor either AC single phase (50-400Hz) or DC voltages. No supply (input) voltage


The pick-up voltage setting is user-adjustable from 85-115% of the nominal voltage rating. As standard, the drop-out voltage setting is fixed at 3% below the pick-up voltage setting. The relay is energized when the monitored voltage is above the pick-up setting. The relay de-energizes when the monitored voltage is below the drop-out







^{*} Fixed at 3% below the pick-up setting.

Voltage Monitoring, DPDT, 10 Amp, AC & DC Relay.



DPDT, 2 Form "C"





Electrical Specifications

Contact

Rating: 10 Amps resistive at 240VAC, 1/2 HP at 240VAC,

10 Amps resistive at 30VDC Life: 500,000 operations at full load

Mechanical Life: 7,000,000 operations at no load

Operational Characteristics

Voltage Settings: .. Pick-up: Adjustable from 85-115% of nom Drop-out: Fixed at 3% below pick-up setting

Setting Accuracy: +0%, -5% min; +5%, -0% max Timing Values: Operate Time: 50 mS Release Time: 50 mS

Power Required: 3VA

Protection

Transient: 10,000V for 20µs

Indicator LED: Red LED on when relay is energized

Reset: Automatic

Environmental Characteristics

Operating: -28°C to +65°C

ACCESSORIES		
MOUNTING STYLES	DESCRIPTION	NTE TYPE NO.
SURFACE MOUNT	8-PIN OCTAL	R95-101
PANEL MOUNT	8-PIN OCTAL	R95-118
DIN RAIL MOUNT	8-PIN OCTAL	R95-113