


**Inóulated Ferruleó (BULK)**

Standard ferruleó conform to uóe on AWG and DIN wire óizeó.  
DIN ferruleó conform to uóe on DIN wire óizeó only.

**Technical Data:**  
DIN/VDE 46228 part 4  
Inóulator: Polypropylene DS10 w/10ppm Silicon  
Contact: Tin-Plated Copper (E-Cu 57)  
Heat reóiant up to 230° F (110° C)  
UL94 Flame Claóo HB, UL# 983438-002



Standard Part No.	DIN Part No.	Nominal wire óize (mm²)	AWG	L1	L2	d1	d2	Quantity/package	Type
902574 light blue		0.25	24	10	6	0.8	1.8	500	H 0.25/10
902576		0.25	24	12	8	0.8	1.8	500	H 0.25/12
902575 turquoioé	902577	0.34	22	10	6	0.8	2	500	H 0.34/10
40950 orange	901900	0.5	20	12	6	1	2.6	500	H 0.5/12
69070 902587	901901 901902	0.5	20	14	8	1	2.6	500	H 0.5/14
40960 white	901903	0.75	18	12	6	1.2	2.8	500	H 0.75/12
46290 902586	901904	0.75	18	14	8	1.2	2.8	500	H 0.75/14
902587 902591	901905 901906	0.75	18	16	10	1.2	2.8	500	H 0.75/16
40970 yellow	901907	1	18	12	6	1.4	3	500	H 1/12
46300 902595	901908	1	18	14	8	1.4	3	500	H 1/14
902593	901910 901911	1	18	16	10	1.4	3	500	H 1/16
46310 red	901912	1.5	16	14	8	1.7	3.5	500	H 1.5/14
63510 56560	901913 901915	1.5	16	16	10	1.7	3.5	500	H 1.5/16
56560 901916	901916	2.5	14	14	8	2.2	4.2	500	H 2.5/14
901917 blue	901917 901918	2.5	14	18	12	2.2	4.2	500	H 2.5/18
901918	901918	2.5	14	24	18	2.2	4.2	500	H 2.5/24
901919 gray	901919	4	12	17	10	2.8	4.8	500	H 4/17
901920 901921	901920 901921	4	12	20	12	2.8	4.8	500	H 4/20
901921	901921	4	12	26	18	2.8	4.8	500	H 4/26
53350 black	901922	6	10	20	12	3.5	6.3	100	H 6/20
56570	901923	6	10	26	18	3.5	6.3	100	H 6/26
53420 ivory	901924	10	8	22	12	4.5	7.6	100	H 10/22
56580	901925	10	8	28	18	4.5	7.6	100	H 10/28
56590 green	901926	16	6	24	12	5.8	8.8	100	H 16/24
56600	901927	16	6	28	18	5.8	8.8	100	H 16/28
31700 brown	901928	25	4	30	16	7.3	11.2	50	H 25/30
31710	901930	25	4	36	22	7.3	11.2	50	H 25/36
31720 beige	901931	35	2	30	16	8.3	12.7	50	H 35/30
31730	901933	35	2	39	25	8.3	12.7	50	H 35/39
44420 olive	901934	50	1,1/0	36	20	10.3	15	50	H 50/36
902820 yellow		70	2/0	37	20	12.7	16	25	H 70/40
red	902821	95	3/0	44	25	14.7	18	25	H 95/44
blue	902822	120	4/0	50	30	16.5	21	25	H 120/50


\* To convert millimeteró (mm) to incheó, uóe formula:  $\frac{XX}{mm} = XX$  incheó  
25.4

**Inóulated Ferruleó (BULK)**

Ferruleó conform to uoe with AWG and DIN wire óizeó.

## Technical Data:

DIN/VDE 46228 part 4  
 Inóulator: Polypropylene DS10 w/10ppm Silicon  
 Contact: Tin-Plated Copper (E-Cu 57)  
 Heat reóistant up to 230° F (110° C)  
 UL94 Flame Claó HB, UL# 983438-002



Mió.	Nominal wire óize (mm²)	AWG	Dimenóionó (mm)*				Quantity/ package	Type	
			L1	L2	d1	d2			
yellow	902101	0.25	24	10	6	0.8	1.8	500	H 0.25/10
	902102	0.25	24	12	8	0.8	1.8	500	H 0.25/12
light blue	902103	0.75	18	12	6	1.2	2.8	500	H 0.75/12
	902104	0.75	18	14	8	1.2	2.8	500	H 0.75/14
	902105	0.75	18	16	10	1.2	2.8	500	H 0.75/16
	902106	0.75	18	18	12	1.2	2.8	500	H 0.75/18
blue	133310	2.5	14	14	8	2.2	4.0	500	H 2.5/14S
	902107	2.5	14	14	8	2.2	4.2	500	H 2.5/14
gray	902108	2.5	14	18	12	2.2	4.2	500	H 2.5/18
	902109	2.5	14	24	18	2.2	4.2	500	H 2.5/24
orange	902110	4	12	17	10	2.8	4.8	500	H 4/17
	902111	4	12	20	12	2.8	4.8	500	H 4/20
	902112	4	12	26	18	2.8	4.8	500	H 4/26
green	902113	6	10	20	12	3.5	6.3	100	H 6/20
	902114	6	10	26	18	3.5	6.3	100	H 6/26
brown	902115	10	8	22	12	4.5	7.6	100	H 10/22
	902116	10	8	28	18	4.5	7.6	100	H 10/28
white	902117	16	6	24	12	5.8	8.8	100	H 16/24
	902118	16	6	28	18	5.8	8.8	100	H 16/28
black	902119	25	4	30	16	7.3	11.2	50	H 25/30
	902120	25	4	36	22	7.3	11.2	50	H 25/36

\* To convert millimeteró (mm) to incheó, uoe formula:  $\frac{XXmm}{25.4} = XX \text{ incheó}$


**Inóulated Ferruleó (STRIPS)**

For uoe with Stripax® Pluó (902000) on pageo 102.

Standard ferruleó conform to uoe on AWG and DIN wire óizeó.  
DIN ferruleó conform to uoe on DIN wire óizeó only.

## Technical Data:

DIN/VDE 46228 part 4  
 Inóulator: Polypropylene DS10 w/10ppm Silicon  
 Contact: Tin-Plated Copper (E-Cu 57)  
 Heat reóistant up to 230° F (110° C)  
 UL94 Flame Claó HB, UL# 983438-002



Standard Part No.	DIN Part No.	Mió. Part No.	Nominal wire óize (mm²)	AWG	Dimenóionó (mm)*				Quantity/ package	Type
					L1	L2	d1	d2		
orange	900427	900428	900428	0.5	20	15	8	1	2.6	500** H 0.5/14
white	900429	900430	900431	0.75	18	15	8	1.2	2.7	500** H 0.75/14
yellow	900432	900433	900433	1	18	15	8	1.4	3	500** H 1.0/14
red	900434	900435	900435	1.5	16	15	8	1.7	3.2	500** H 1.5/14
blue	900436	900436	900437	2.5	14	15	8	2.2	4	500** H 2.5/14

\* To convert millimeteró (mm) to incheó, uoe formula:  $\frac{XXmm}{25.4} = XX \text{ incheó}$

\*\* 10 ótripó of 50 each

## Uninulated Ferruleo (BULK)

Ferruleo conform to size on AWG and DIN wire size.

**Technical Data:**  
 DIN/VDE 46228 part 4  
 Contact: Tin-Plated Copper (E-Cu 57)  
 Heat resistant up to 230° F (110° C)  
 UL94 Flame Class HB  
 UL# 983438-002




Wire size (mm²)	AWG	Dimension (mm)*			Quantity/package	Type	Part Number
		A	B	C			
0.25	24	5	0.7	1.65	1000	H 0.25/5	901891
0.5	20	6	1	2.1	1000	H 0.5/6	28260
0.5	20	10	1	2.1	1000	H 0.5/10	900405
0.75	18	6	1.2	2.3	1000	H 0.75/6	28270
0.75	18	10	1.2	2.3	1000	H 0.75/10	54250
1	18	6	1.4	2.5	1000	H 1/6	37260
1	18	10	1.4	2.5	1000	H 1/10	28280
1.5	16	7	1.7	2.8	1000	H 1.5/7	37270
1.5	16	10	1.7	2.8	1000	H 1.5/10	18650
1.5	16	12	1.7	2.8	1000	H 1.5/12	900406
1.5	16	18	1.7	2.8	1000	H 1.5/18	900407
2.5	14	7	2.2	3.4	1000	H 2.5/7	37300
2.5	14	10	2.2	3.4	1000	H 2.5/10	900408
2.5	14	12	2.2	3.4	1000	H 2.5/12	18610
2.5	14	18	2.2	3.4	1000	H 2.5/18	900409
4	12	9	2.8	4	500	H 4/9	37310
4	12	12	2.8	4	1000	H 4/12	24410
4	12	15	2.8	4	500	H 4/15	900410
4	12	18	2.8	4	500	H 4/18	900411
6	10	10	3.5	4.7	500	H 6/10	900412
6	10	12	3.5	4.7	500	H 6/12	19190
6	10	15	2.8	4	500	H 6/15	12470
6	10	18	2.8	4	500	H 6/18	900413
10	8	12	4.5	5.8	500	H 10/12	28290
10	8	15	4.5	5.8	500	H 10/15	12480
10	8	18	4.5	5.8	500	H 10/18	37930
16	6	12	5.8	7.5	500	H 16/12	49250
16	6	15	5.8	7.5	500	H 16/15	12430
16	6	18	5.8	7.5	100	H 16/18	37520
16	6	25	5.8	7.5	500	H 16/25	900415
16	6	32	5.8	7.5	500	H 16/32	900416
25	4	15	7.3	9.5	250	H 25/15	12440
25	4	18	7.3	9.5	100	H 25/18	37530
25	4	25	7.3	9.5	100	H 25/25	900417
25	4	32	7.3	9.5	100	H 25/32	900418
35	2	18	8.3	11	100	H 35/18	36890
35	2	25	8.3	11	100	H 35/25	900419
35	2	30	8.3	11	100	H 35/30S	945100
35	2	32	8.3	11	100	H 35/32	900420
50	1,1/0	18	10.3	13	100	H 50/18	900421
50	1,1/0	25	10.3	13	100	H 50/25	902588
50	1,1/0	32	10.3	13	100	H 50/32	900422

\* To convert millimeter (mm) to inch, use formula:  $\frac{XXmm}{25.4} = XX \text{ inch}$

## Inóulated Ferruleó (RETAIL PACKAGING)

For ferrule dimension, see chart on page 104



AWG	Part No.	Content	Color
20	9107	100 piece of 69070	orange
18	9129	100 piece of 46290	white
18	9130	100 piece of 46300	yellow
16	9131	100 piece of 46310	red
14	9132	100 piece of 901916	blue
12	9133	100 piece of 901920	gray
10	9135	100 piece of 53350	black
8	9142	100 piece of 53420	ivory
6	9159	100 piece of 56590	green

### Technical Data:


DIN/VDE 46228 part 4  
Contact: Tin-Plated Copper (E-Cu 57)  
Heat resistant up to 230° F (110° C)  
UL94 Flame Class HB  
UL# 983438-002

## Dual-Wire Ferruleó (BULK)

Standard ferruleó conform to use on AWG and DIN wire sizes.  
DIN ferruleó conform to use on DIN wire sizes only.

## Uninóulated Ferruleó (RETAIL PACKAGING)

For ferrule dimension, see chart on page 105




AWG	Part No.	Content
20	9226	100 piece of 28260
18	9225	100 piece of 54250
18	9228	100 piece of 28280
16	9265	100 piece of 18650
14	9261	100 piece of 18610
12	9241	100 piece of 24410
10	9219	100 piece of 19190
8	9293	100 piece of 37930
6	9243	100 piece of 12430

### Technical Data:

DIN/VDE 46228 part 4  
Contact: Tin-Plated Copper (E-Cu 57)  
Heat resistant up to 230° F (110° C)  
UL94 Flame Class HB  
UL# 983438-002

### Technical Data:

DIN/VDE 46228 part 4  
Contact: Tin-Plated Copper (E-Cu 57)  
Heat resistant up to 230° F (110° C)  
UL94 Flame Class HB  
UL# 983438-002



Standard Part No.	DIN Part No.	Mioc. Part No.	Nominal wire size (mm²)	2 Wire/ Ferrule AWG				Dimenión (mm)†		Qty/ pkg.	Type
				L1	L2	d1	A/B				
900444*** orange	900478*** white		0.5	20	14.6	8.2	1.4	5/3	500	H 0.5/15	
901851*** white	901852*** gray	901857*** light blue	0.75	18	14.6	8.2	1.7	5.5/3	500	H 0.75/15	
	900477***		0.75	18	16.4	10	1.7	5.5/3	500	H 0.75/17	
901853*** yellow	901854*** red	900476***	1.0	18	15.0	8.0	2.0	5.8/3.2	500	H 1.0/15	
			1.0	18	19.0	12	2.0	5.8/3.2	500	H 1.0/20	
900441*** red	900442*** black		1.5	16	15.8	8.2	2.3	6.5/3.6	500	H 1.5/16	
	900475*** black		2.0	16	19.6	12	2.3	6.5/3.6	500	H 1.5/20	
900443* blue	900443* blue	901858*	2.5	14	18.5	10	2.9	8/4.5	250	H 2.5/18.5	
900474** gray	900474** gray	901859** orange	2.5	14	20.5	12	2.9	8/4.5	100	H 2.5/20.5	
			4.0	12	22	12	3.5	9/5.2	100	H 4/22	

Thee ferruleó are packaged in tear-off perforated packó attached to a hanger.

\*5 packó of 50 each

\*\* 5 packó of 20 each

\*\*\* 5 packó of 100 each

† To convert millimeteró (mm) to incheó, use formula:  $\frac{XXmm}{25.4} = XX \text{ incheó}$