

Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

# Model #: HT706TV

7 outlet, 6ft corded strip, 1080 joules, coaxial protection - Home/Business Theater Suppressor



# **Highlights**

- 7 outlets / 6 ft. cord
- 1080 joule rating
- · Coaxial surge protection
- \$50,000 Ultimate Lifetime Insurance (USA and Canada only)

# **Description**

Tripp Lite's HT706TV Home/Business Theater Surge Suppressor provides high-performance protection--1080 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 7 outlets (with transformer spacing) and 1-line coaxial protection safeguard an entire home/business theater system. \$50,000 Ultimat Ultimate Lifetime Insurancecoverage (USA & Canada only). Includes two diagnostic LEDs, 6 ft. cord with a right-angle plug and 6 ft. coaxial cable.

#### Applications

• Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

# Package Includes

- HT706TV Home/Business Theater Surge Suppressor
- 6 ft. coaxial cable
- Instruction manual with warranty information

# **Features**

- 1080 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$50,000 Ultimate Lifetime Insurance (USA & Canada only) covers connected components against surge damage...for life!
- 7 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely-spaced outlets accommodate up to 4 transformers
- 1 set of Type F surge-protected coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line
- 6 ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 2 diagnostic LEDs alert user to protection and grounding status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Integrated circuit breaker protects against dangerous system overload
- High-impact plastic housing (black) stands up to the most demanding environments
- UL and CSA listed

# **Specifications**

OVERVIEW		
Intended Application	Audio/Video	
SYSTEM OVERVIEW		
Voltage compatibility	120 VAC	
ОИТРИТ		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Output volt amp capacity (amps)	15	
Outlet quantity / type	7 NEMA 5-15R	
Transformer accommodation	Accommodates 4 transformers	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input plug features	Space-saving right angle input plug	
Input cord length (ft.)	6	
Input cord length (m)	1.8	
Input cord gauge, type	14 gauge, SJT	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LEDs	Built-in LEDs confirm protection and grounding status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	1080	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	150V	
UL1499 let through rating	330V - UL verified	
EMI / RFI filtering	Up to 40 dB	
DATALINE SURGE SUPPRESSI	ON	
Telephone/DSL Protection	No	
Cable (Coax) Protection	Yes	
Cable (Coax) Protection Details	1 line	
Network (Ethernet) Protection	No	

PHYSICAL	
Shipping weight (lbs)	5.02
Shipping weight (kg)	2.28
Unit Dimensions (HWD/in)	1.5 x 14 x 2.75
Unit Dimensions (HWD/cm)	3.8 x 35.6 x 7
Shipping Dimensions (HWD/in)	2 x 15 x 6
Shipping Dimensions (HWD/cm)	5.1 x 38.1 x 15.2
Unit weight (lbs)	1
Unit weight (kg)	0.45
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting
AC line cord color	Black
Style	Strip
SPECIAL FEATURES	
Right-Angle Plug	Yes
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
cUL / CSA (Canada)	CSA
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2811.