Technical Data Sheet Plenum Communication Cables

WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

25293B **PART NUMBER:**

DESCRIPTION: 18/2 Stranded bare copper conductors, shielded with an overall jacket.

NEC RATING: CMP, NEC Article 800

APPROVALS: (UL) C(UL) Listed

Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems, APPLICATION:

Security Systems, Sound, Audio, Background Music)

Construction Parameters:

Conductor 18 AWG Bare Copper

Stranding 7x26

Insulation Material Low Smoke PVC 0.008" Nom. Insulation Thickness

Number of Conductors

Shield 100% Aluminum Polvester Foil Stranded Tinned Copper 24 AWG Drain

Jacket Material Low Smoke PVC Jacket Thickness 0.015" Nom.

Rip cord Yes

Overall Cable Diameter 0.156" Nom. Approximate Cable Weight 21 Lbs/1M' Nom.

Flame Rating NFPA 262 Flame Test 800

NEC Article

Electrical & Environmental Properties:

Temperature Rating -10°C To +60°C Operating Voltage 300 V RMS

Max.Capacitance Between Conductors @ 1 KHz 68 pf/ft Nom. Capacitance Between Conductors to Shield @ 1 KHz 122 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 6.2 Ohms/1M' Nom.

Nom. Inductance .15uH/ft **Insulation Colors** Black, Red Jacket Color Gray, Yellow, Blue, Black

25293B, 25293B-YE

Mechanical Properties:

Max. Recommended Pull Tension Min. Bend Radius (Install)

Put ups:

Advantage Box 500ft. Advantage Box 1000ft.

Revision 2: 6/10 Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

57 lbs 1.6"



Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.