

3528 Size Flexible LED Strips

Features

- Available in 3 Different Waterproof Ratings
Non-Waterproof (IP20)
Water Resistant (IP65)
Waterproof (IP68)
- Adhesive Back, Peel & Stick (EXCLUDING WP Suffix)
- Available in 100 Ft (30.48 Meter) Reels, 16.4 Ft. (5 Meter) Reels, and 19.69 In (0.5 Meter) Pre-Cut Strips
- Standard 16.4 Ft. (5 Meter) Reels can be cut to smaller lengths
- Pre-Cut 19.69 In (0.5 Meter) Strips come Pre-Wired with a 69-A1 Connector already Attached
- 2 Different LED Densities
30/Strip or 60/Strip (0.5 Meter Lengths)
300/Reel or 600/Reel (5 Meter Lengths)
- RoHS Compliant
- Very Bright and Low Power Consumption
- Dimmable to 6V DC
- Applications Include: Interior Lighting, Ceilings, Shelves, Cabinets, Showcases, Motor Homes, RV's, Boats and Aviation



Specifications

Viewing Angle: 120°

Voltage: 12V DC (69-36W-100-24 is 24V)

Wattage per Reel:

30 LED Count: 2.4W

60 LED Count: 4.8W

300 LED Count: 24W

600 LED Count: 48W

Operating Temperature: -20° to +50°C

Storage Temperature: -30° to +80°C

Life Span: 50,000 hours min

Ordering Information

Non-Waterproof Types

NTE Type No.				LED Color	Luminous Intensity (per LED)	WL (nm) & CCT (K)
5 Meter Length		1/2 Meter Length				
300 / Reel	600 / Reel	30 / Strip	60 / Strip			
69-36R	69-312R	69-36R-02	69-312R-02	Red	400mcd	620 - 630nm
69-36A	69-312A	69-36A-02	69-312A-02	Amber	400mcd	585 - 595nm
69-36B	69-312B	69-36B-02	69-312B-02	Blue	300mcd	455 - 470nm
69-36G	69-312G	69-36G-02	69-312G-02	Green	800mcd	510 - 525nm
69-36PI	69-312PI			Pink	450mcd	452.5 - 455nm
69-36PU	69-312PU			Purple	450mcd	385 - 400nm
69-36W **	69-312W	69-36W-02	69-312W-02	White	4lm	6000 - 7000K
69-36WWW	69-312WWW	69-36WWW-02	69-312WWW-02	Warm White	4lm	3000 - 3500K

Also available in 100 ft. lengths - check with factory.

** The 100 ft. length is available in either 12V or 24V.

NOTE: LED strips should not be used in sealed environments or in areas where ambient temperatures are extremely hot.

Epoxy Water Resistant Types

NTE Type No.				LED Color	Luminous Intensity (per LED)	WL (nm) & CCT (K)
5 Meter Length		1/2 Meter Length				
300 / Reel	600 / Reel	30 / Strip	60 / Strip			
69-36R-WR	69-312R-WR	69-36R-WR-02	69-312R-WR-02	Red	400mcd	620 - 630nm
69-36A-WR	69-312A-WR	69-36A-WR-02	69-312A-WR-02	Amber	400mcd	585 - 595nm
69-36B-WR	69-312B-WR	69-36B-WR-02	69-312B-WR-02	Blue	300mcd	455 - 470nm
69-36G-WR	69-312G-WR	69-36G-WR-02	69-312G-WR-02	Green	800mcd	510 - 525nm
69-36PI-WR	69-312PI-WR			Pink	450mcd	452.5 - 455nm
69-36PU-WR	69-312PU-WR			Purple	450mcd	385 - 400nm
69-36W-WR	69-312W-WR	69-36W-WR-02	69-312W-WR-02	White	4lm	6000 - 7000K
69-36WWW-WR	69-312WWW-WR	69-36WWW-WR-02	69-312WWW-WR-02	Warm White	4lm	3000 - 3500K

NOTE: LED strips should not be used in sealed environments or in areas where ambient temperatures are extremely hot.

3528 Size Flexible LED Strips

Silicon Tube and Waterproof Types

NTE Type No.		LED Color	Luminous Intensity (per LED)	WL (nm) & CCT (K)
300 / Reel	600 / Reel			
69-36R-WP	69-312R-WP	Red	400mcd	620 – 630nm
69-36A-WP	69-312A-WP	Amber	400mcd	585 – 595nm
69-36B-WP	69-312B-WP	Blue	300mcd	455 – 470nm
69-36G-WP	69-312G-WP	Green	800mcd	510 – 525nm
69-36PI-WP	69-312PI-WP	Pink	450mcd	452.5 – 455nm
69-36PU-WP	69-312PU-WP	Purple	450mcd	385 – 400nm
69-36W-WP	69-312W-WP	White	4lm	6000 – 7000K
69-36WW-WP	69-312WW-WP	Warm White	4lm	3000 – 3500K

NOTE: LED strips should not be used in sealed environments or in areas where ambient temperatures are extremely hot.

Dimensions

