


TIPS

ET SERIES TIPS FOR PES51 SOLDERING PENCIL TINNED WITH LEAD FREE SOLDER


THE WELLER ADVANTAGE:

The sensor hole in the base of the tip is fitted with a stainless steel liner to prevent the tip from seizing to the sensor.




SCREWDRIVER

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETA*	0.062	1.60	0.032
ETB*	0.093	2.40	0.020
ETC*	0.125	3.20	0.027
ETD	0.187	4.80	0.035
ETH	0.031	0.80	0.019




LONG SCREWDRIVER

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETJ	0.031	0.80	0.012
ETK*	0.046	1.20	0.026
ETL	0.078	2.00	0.027
ETM	0.125	3.20	0.037




NARROW SCREWDRIVER

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETR	0.062	1.60	0.044




CONICAL

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETP*	0.031	0.80	0.012
ETT	0.024	0.60	0.036




LONG CONICAL

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETO*	0.031	0.80	0.044
ETS*	0.015	0.40	--



SINGLE FLAT

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETAA	0.062	1.60	0.040
ETBB	0.093	2.40	0.032
ETCC	0.125	3.20	0.032
ETDD	0.187	4.80	0.032
ETU	0.015	0.40	--
ETV	0.024	0.60	--



KNIFE

Cat No.	A IN. MM	B IN. MM	C IN. MM
ETKN	0.180	4.57	0.064