

Technical Data Sheet

Plenum Communication Cables



2833 West Chestnut Street
 Washington, PA 15301
 Toll Free: (800) 245-4964
 Fax: (724) 222-6420
 www.westpenn-wpw.com

PART NUMBER:	25224B
DESCRIPTION:	18/2 Stranded bare copper conductors, unshielded with an overall jacket.
NEC RATING:	CMP, NEC Article 800
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems, Security Systems, Sound, Audio, Background Music)

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	7x26
Insulation Material	Flex Plenum PVC
Insulation Thickness	0.008" Nom.
Number of Conductors	2
Shield	None
Drain	None
Jacket Material	Flex Plenum PVC
Jacket Thickness	0.015" Nom.
Overall Cable Diameter	0.154" Nom.
Approximate Cable Weight	17 Lbs/1M' Nom.
Flame Rating	NFPA 262 Flame Test

Electrical & Environmental Properties:

Temperature Rating	-10°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	30 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	6.2 Ohms/1M' Nom.
Insulation Colors	Black, Red
Jacket Color	Gray, Black, Brown, Orange, Green White, Yellow
RoHS Compliant	Yes

Mechanical Properties:

Max. Recommended Pull Tension	42 lbs
Min. Bend Radius (Install)	1.4"



Specification Issue Date: 7/06

This document is the property of West Penn Wire.
 The information contained herein is considered
 Proprietary and not to be reproduced by any means
 Without written consent of West Penn Wire

Standard Lengths are 1000ft.
 The Jacket is sequentially footmarked.
 The information presented here is, to the best of our
 knowledge, is true and accurate. However, since
 conditions of use are beyond our control, all
 recommendations or suggestions are presented
 without guarantee or responsibility on our part. We
 disclaim all liability in connection with the use of
 information contained herein or otherwise.